

SPS-866B

ACTIVE MEDIA SPEAKERS (20 WATTS PER CHANNEL)



TECHNICAL SPECIFICATION

OUTPUT POWER:	20W + 20W (RMS)
P.M.P.O:	600W
SPEAKER UNIT:	Tweeter : 1.5" (shielded) Dual woofer : 5" (shielded)
IMPEDANCE:	4 (OHM)
FREQUENCY RESPONSE:	Amplifier : 20Hz to 20KHz Speaker : 30Hz to 18KHz
INPUT PORT:	2 x RCA
TREBLE ADJUST:	+ 10dB
BASS ADJUST:	+ 10dB
SEPARATION:	• 45 dB
S/N RATION:	• 75 dB
DIMENSION:	(166 x 233 x 335)mm
WEIGHT:	7600g
POWER SUPPLY:	AC 220V 50/60Hz
ACCESSORY:	1x Speaker connection cable and 1x 2RCA cable

SPS-A030A

2-WAY INDOOR POWERED SPEAKERS (30 WATTS PER CHANNEL)



TECHNICAL SPECIFICATION

Ideal for monitor, AV applications
Stereo inputs RCA mini stereo jack
Stylish design, suited for place everywhere
Good at efficiency

POWER CAPACITY:	2x30 Watts
FREQUENCY RANGE:	100Hz-20kHz
IMPEDANCE:	4 Ohm
SENSITIVITY:	88dB
WOOFERS:	5 1/4" Polypropylene
DIMENSIONS(HWD):	240 x 178 x 170 mm

SPS-S025A1

SPEAKER SYSTEM WITH ECO DIGITAL AMPLIFIER (25WATTS PER CHANNEL)



TECHNICAL SPECIFICATION

- Integrated with switching power supply unit for best power efficiency
- Integrated with digital amplifier for low power consumption
- Integrated with input signal sensing for auto power ON/OFF to maximum power efficiency
- Fully eco friendly speaker system

OUTPUT POWER:	2x25 Watts
FREQUENCY RANGE:	20Hz to 20KHz (Amplifier) 30Hz to 18KHz (Speaker)
IMPEDANCE:	4 Ohm
SENSITIVITY:	88dB
WOOFERS:	6 1/2" PP cone
DIMENSIONS(HWD):	288 x 215 x 180 mm

* Specifications are subject to change without notice.

ABTUS