

AVA-HDMI 1 8

HDMI Distribution Amplifier
(1-In 8-Out HDMI)



Supports up to
1080p
HDCP
Compliant



DESCRIPTION

The **ABtUS AVA HDMI 18** is a high quality 1 input 8 output distribution amplifier for HDMI signal. **ABtUS AVA HDMI 18** distributes a HDMI source up to 8 HDMI digital display devices (Projectors, Plasma and LCD Monitors) with excellent identical reproduction. It supports a wide range of PC and HDTV resolutions from VGA to YXGA and 480p to 1080p.

SPECIFICATIONS

Video Amplifier Bandwidth	1.65 GHZ
Input Video Signal	1.2 volts p-p
Input DDC Signal	5 volts p-p(TTL)
Maximum Single Link	Range 1920*1200, A1080p
Input/Output	Connector Type 19 Pin HDMI
Audio Output	TOSLINK
Power Consumption	12 Watts (MAX)
Power Supply	12V DC
HDMI 1*8	Increase Input Cable Length up to 20M (MAX) Output Cable Length up to 25M (MAX)

TYPICAL APPLICATIONS

The **ABtUS AVA HDMI 18** is part of the ABtUS series of high quality, high bandwidth and cost effective distribution amplifiers specially for professional installers. ABtUS products can be found in industrial, commercial retail and home applications like:

- Production Studios ➤ Rental and Staging ➤ Home Theatres
- Live Broadcast or Presentation Applications

