

SMC-TX2 & SMC-RX SMART-Connect Full HD



SMC-TX2



SMC-RX

SMART-Connect is a wireless video transmission device. SMART-Connect uses mirroring technology to transmit video and audio from laptop or hand-held devices to TV, Monitor or projector.

It is ideal tools for wireless business meetings, presentations and classrooms.

Features

- SMART-CONNECT can transmit video and audio from laptop or hand-held devices to TV, Monitor or projector.
- Real-time high quality video & sound transmission
- Actual mirroring technology showing all contents as it is.
- Devices can be easy just by clicking on the transmitter
- Connect up to 254 TX2 to a single RX

Technical specification

	SMC-TX2 (Transmitter)	SMC-RX (Receiver)
Transmission quality:	Video: support 1080p Sound: Mono, Stereo supported Frequency: 5.2GHz	Video: support 1080p Sound: Mono, Stereo supported Frequency: 5.2GHz
Compatible device:	HDMI supported PC, camcorders and game console, smartpads and smartphones supported if HDMI converters is connected	HDMI support devices (LCD TV, Monitors, Interactive display boards, projectos, etc.)
Interface:	HDMI	HDMI
Communication:	Directly connect of Wlan 802.11/n 5GHz with receiver	Directly connect of Wlan 802.11/n 5GHz with transmitter
Components:	Smart-Connect Transmitter HDI extension cable USB power cable	Smart-Connect Receiver HDX extension cable USB power cable
Power:	Built in rechargeable battery, DC5V	Uses external power supply through micro USB DC5V
Product dimension :	82 x 72 x 20 mm	110 x 30 x 10 mm
RF frequency range :	5.15GHz --- 5.82GHz	5150 to 5825 MHz (20 Mhz)
Channel frequency :		36 (5180), 44 (5220), 48 (5240), 149 (5745), 153 (5765), 157 (5785), 161 (5805)
RF output power (5G) :	802.11n HT20 mask compliant 14dBm@ MCS7	11n HT20 mask compliant -64dBm@ MCS7
Power consumption :	802.11n HT20 / 317mA (5G)	802.11n HT20 / 210mA
Operating temperature :	0 to 55°C	0 to 55°C

SMC-TX2 & SMC-RX

SMART-Connect Full HD

Diagram



Optional: Charging Station (SMC-CHARG-STN2)



FEATURES

- Storing 3 transmitters and accessories
- Charging 3 transmitters simultaneously (time for charging: Approx. 2.5Hrs)
- Able to store HDMI extension cable and converter