

## ZW-18AWG SPK CB (150M , 300M & 500M) Speaker Cable



### Features

- Cable Type: 18AWG\*2C Speaker Cable
- Packaging: 150m wooden roll; 300m wooden roll; 500m wooden roll
- Operating Temperature: -20°C THRU 75°C

### Technical specification

#### Materials

Nom. Conductor O.D.:	7*0.4+0.01mm
Conductor Material:	Tinned Copper
Nom. Insulation O.D.:	2.32+0.1mm
Insulation Material:	PVC, Color in Black and White
Nom. Cabling Lay length:	47+10mm
Nom. Jacket O.D.:	6.02+0.3mm
Min Jacket Thickness:	0.50mm
Jacket Material:	Grey PVC, CM
Rip Cord:	3*500D

#### Electrical Characteristics

Nom. Conductor Resistance(@20°C):	≤21.5Ω/km(6.5 Ohm/kft)
Nom. Capacitance Cond-to-Cond	22pF/ft
Max. Current	4.8 Amps Per Cond at 25°C
Voltage Rating	300V
Insulation Resistance(@20°C in Air):	≥200MΩ·km
Insulation Withstanding Spark Voltage:	AC 3000V
Jacket Withstanding Spark Voltage:	AC 3000V

#### Packaging

150m	Roll Size: 280mm(L)*100mm(W)*200mm(H) Pallet: 1120*1120*130mm; 4(L)*4(w)*5(H)=80 rolls/pallet,H=1.13M
300m	Roll Size: 280mm(L)*100mm(W)*280mm(H) Pallet: 1120*1120*130mm; 4(L)*4(w)*3(H)=48 rolls/pallet,H=0.97M
500m	Roll Size: 340mm(L) * 100mm(W) *300mm(H) Pallet: 1020* 1020* 130mm; 3(L) *3(w)*3(H)=27 rolls/pallet,H= 1.03M