

# SMC-PS02

## SafeEntry & TraceTogether Quick Scanner

---



**SMC-PS02** Presentation scanner provides quick and easy capture of 1D and 2D barcodes, including tiny and high density codes. This hands-free omni directional scanner allows faster scan rates with less aiming due to its wider reading areas.

Smart Connect Barcode scanners provide easy-to-use, rapid and accurate scanning for retailers, SMEs, schools and government departments and warehouses around the world.

### Features

---

- Plug & Play for quick and hassle-free set up
- No software/driver required
- Fast Scanning
- Supports 1D and 2D barcodes (including QR code)
- Big scan window allows quick and efficient scanning
- Able to scan both **TraceTogether Token** and **NRIC**

# SMC-PS02

## SafeEntry & TraceTogether Quick Scanner

---

### Technical Specification

---

#### **Scanning Method:**

Auto Mode

Sensor:

752\*480 CMOS

Lighting:

White LED

Reading precision:

(≥ 5MIL)

Visual Indicator:

LED & Buzzer

#### **Supported Barcode**

1D Bar Code:

Code 39, Code 93, Code 128, UCC/EAN 128, Codabar, Interleaved 2 of 5, AIM-128, EAN-8, EAN-13, ISBN/ISSN, UPC-A, RSS-Expand, ITF-6, ITF-14, Matrix 2 of 5, Industrial 25, Standard 25, Code 11, Plessey, MSI-Plessey, GS1-DataBar (RSS), (RSS-14, RSS-Limited)

2D Bar Code:

QR Code, Data Matrix, PDF417, Hanxin Code

#### **Interface**

Communication Interface:

USB

#### **Electrical**

Input Voltage:

DC 5V

Working current:

240mA

#### **Environmental Parameters**

Working Temperature:

20°C - +50°C

Storage Temperature:

-40°C - +80°C

Relative Humidity:

5%~ 95% (Non-condensing)

Drop/Shock Resistance:

Withstands multiple time 1.2 meters drop to concrete

Protection level:

IP52

#### **Mechanical**

Dimension:

106 X 111 X 155 mm (L x W x H)

Weight:

320g

#### **Packaging**

Comes with:

1 x Presentation Scanner, 1 x USB cable