

## DAN-AIN

### Dante Dongle 2CH Analog Input



The ABtUS DAN-AIN provides seamless connection of analog audio sources to any Dante-enabled system. With 2-channel analog audio input, it enables direct integration of microphones, mixers, and other analog devices into the Dante network. Compact, plug-and-play, and hassle-free.

#### Features

- Plug and Play
- 24-bit audio support
- 2 Audio channels
- Supports 802.3af PoE

#### Technical specification

##### Audio

Max signal level	+24 dBu
Frequency Response	20Hz to 20kHz(-/+0.5dB)
Impedance	20k Ohm balanced 10k Ohm unbalanced
Dynamic Range	>100 dB
Signal to Noise Ratio	>100 dB
THD	<0.01% @+4 dBu

##### Dante

Sample Rate	44.1kHz, 48kHz, 96kHz
Bit Depth	24
Dante Device latency	1,2 or 5ms (configurable using Dante Controller)

##### General

Operation Temperature	-5 to +55°C (+23° to +131°F)
Storage Temperature	-25 to +70°C (-13° to +158°F)
Power	802.3af PoE
Power Consumption	3.15W(Max)
Dimension (W*H*D)	30 x 28 x 114 mm
Cable length	300 mm
Net Weight	145 g