

Dante Dongle USB I/O

User Operation Guide



Model:
DAN-USB

rev.2025.08Aug.21

User Operation Guide

OVERVIEW

The ABtUS **DAN-USB** seamlessly bridges PCs and mobile devices with any Dante-enabled system. With 2x2 channels of bidirectional audio over a simple USB-A/C connection, it enables instant playback and capture of high-quality audio across the Dante network. Compact, plug-and-play, and hassle-free.

PRODUCT FEATURES

- Plug and Play
- 24-bit audio support
- 2X2 audio channel
- Supports 802.3af PoE

PRODUCT FEATURES



No	Name	Function description
1	RJ45:	Dante network communication port. Green steady light \ indicates system ready; yellow flashing light indicates link/ data traffic. The green light will flash to identify the device when clicking the Dante Controller “Identify” button (an eye-shaped symbol) on the host computer.
2	USB-C:	1 x USB-C, compliant USB 2.0 device

TECHNICAL SPECIFICATIONS**Dante**

Power	802.3af PoE
Sample Rate	48 kHz
Bit Depth	24

General

Operation Temperature	-5 to +55°C
Storage Temperature	-25 to +70°C
Power Consumption	9W(Max)
Dimension (W*H*D)	115x 34 x 28 mm
Cable length	20 cm
Net Weight	70 g

