


140W USB-C power injector with HDMI out



Model:

PIN-UC12HU-140W

rev.2026.06June.05

User Operation Guide


OVERVIEW

The **PIN-UC12HU-140W** 140W USB-C power injector with HDMI out

PRODUCT FEATURES

- PD 3.1 w/ 140W injection.
- DP alt mode w/ 4K@60Hz 4:4:4 video.
- Supports SST/MST output.
- USB-C w/ HDMI dual video output.
- Up to 10Gb USB3.2 Gen2 data rate.
- Switchable USB-C OUT power.
- Firmware can be upgrade via USB-C.
- USB-C input w/ locking hole

DIAGRAM



TECHNICAL SPECIFICATIONS

Input	1x USB-C
Output	1x USB-C, 1x HDMI
Video	Input: Up to 4K@60Hz 4:4:4 Output: Up to 4K@60Hz 4:4:4
USB	Data Rate: 10Gbps Device Power: 0 / 15W
PD Standard	PD 3.1
Power Consumption	3W (Exclude USB device load)
Operation Temperature	-5 °C ~ +55 °C
Storage Temperature	-25 °C ~ +70 °C
Relative Humidity	10% ~ 90%
Dimension	70(W) x 20(H) x 90(D) mm
Net Weight	165g

