

AVS-315+ Plus

Programmable Integrated Projector Controller Switcher



The ABtUS **AVS-315+ Plus** Media Control Panel is one of the most user friendly and installer friendly Programmable Controller, specifically designed for a easy and central control of any AV projection system with interactive through USB. It removes the need for over-complicated and multiple remote control handsets. With the 2:1 USB-B switcher, switching for projection with interactive can now be done with just a push of a button.

Features

- "User Programmable" with Window base Application Software
- Simple to used with one to one function controlled button
- Works well with any monitors, projectors as well as interactive system
- Supports 2x2 VGA matrix switching
- Easy Installation with standard 2.54mm connector and cabling
- Fully self contained / integrated Projector Controller with AV switcher
- Build in USB buffer with best connective for interactive system and USB thumb drive

Technical specification

Input:	VGA Input × 2 (*D-Sub 15pin)
	PC-Audio × 2 (*3.5mm)
	C-Video × 1 (*RCA)
	Stereo Audio × 1 (*RCA)
	Microphone × 1 (*3.5mm)
	USB-B × 2 (Switcher with build in buffer)
	USB-A × 1 (for Thumb Drive with build in buffer)
Output:	1 × VGA (*standard 2.54mm connector for Projector)
	1 × VGA output (*D-Sub 15pin for monitor)
	1 × C-Video (*standard 2.54mm connector)
	1 × Main Stereo Audio (*standard 2.54mm connector)
	1 × Tx (*standard 2.54mm connector)
	1 × USB-B
	1 × USB-A
VGA bandwidth:	2x2 VGA Matrix Switching, 900MHz (R+G+B)
Max resolution:	1280 x 1024
All cable length:	Up to 28 meter
Max resolution:	1 x RS-232 (8 Data Bit and 1 Stop Bit)
All cable length:	1200 to 115200
Configuration com port:	Non, Even or Odd (Programmable projector protocol)
Delay time:	Projector "ON/OFF" delay time (*in sec) 1 to 99
Control button:	Number of user defined "Control Button" × 8
	Available protocol for each "Control Button" × 2
LED:	With LED indication and buzzer for confirmation
Video selection:	All Video/VGA Input Switching Digital
Audio selection:	Audio Switching Digital
Volume:	Main Volume Control Analog
Mic gain:	Microphone Input Gain Control Analog
Power adaptor:	12V-DC, 500mA
Housing:	ABS Enclose
Gross dimension:	190 × 195 × 80 mm (without cable kit)
Gross weight:	530 g (without cable kit)

AVS-313

Programmable Integrated Projector Controller Switcher

Typical applications

Any professional presentation system requiring multiple AV Inputs of all different type of Video standard and a standard projector controller.

- Schools (Media Classroom) • Churches • Corporate Applications (Training Room)

Diagram

