

### BTM-S06R & BTM-S05T

#### Bluetooth Microphone Voice Enhancement System



#### FEATURES

**BTM-S05T** Transmitter (3.5mm mono Female connector)

**BTM-S06R** Receiver (6.3mm mono Male plug)

- Plug-N-Play
- High quality transmission
- No movement restriction
- Convenient and portable
- User friendly

#### TECHNICAL SPECIFICATION

**Bluetooth standard:** Bluetooth specification V2.0

**Output power:** Class 1

**Transmission distance:** 35meters (Unobstructed line of sight)

**Battery:** AAA size 4pcs (TX 2pcs, RX 2pcs)

**Battery life:** Approximately 8 hours

**Carrier band frequency:** ISM band 2,400~2,483.5 MHz

**Transmit power:** +5dBm

**Receiver sensitivity:** -85dBm

**Maximum output voltage:** 110mV (RMS)

**Maximum current consumption:** 70mA

**Frequency response:** 25~19KHz (BTM-S05T)

32~19KHz (BTM-S06R)

**Latency:** ~4 ms (Millisecond)

### BTM-S06R & BTM-S06T

#### Bluetooth Microphone Voice Enhancement System



#### FEATURES

**BTM-S06T** Transmitter (XLR Female connector)

**BTM-S06R** Receiver (6.3mm mono Male plug)

- Plug-N-Play
- High quality transmission
- No movement restriction
- Convenient and portable
- User friendly

#### TECHNICAL SPECIFICATION

**Bluetooth standard:** Bluetooth specification V2.0

**Output power:** Class 1

**Transmission distance:** 35meters (Unobstructed line of sight)

**Battery:** AAA size 4pcs (TX 2pcs, RX 2pcs)

**Battery life:** Approximately 8 hours

**Carrier band frequency:** ISM band 2,400~2,483.5 MHz

**Transmit power:** +5dBm

**Receiver sensitivity:** -85dBm

**Maximum output voltage:** 110mV (RMS)

**Maximum current consumption:** 70mA

**Frequency response:** 25~19KHz (BTM-S06T)

32~19KHz (BTM-S06R)

**Latency:** ~4 ms (Millisecond)

\* Specifications are subject to changes without notice.