

CS-08I2 Central Control System



The ABtUS CS-08i2 is a rack mount processor that acts as a central control system for medium to large-scale AV integrations.

The CS-08I has various control ports (RS-232,RS-485, Ethernet, Bi-directional IR, D/I D/O and Relays) that caters for practically any installation. It also comes with an iOS app for wireless control using any iOS supported devices.

Programming is uncomplicated and the various predefined shortcuts allow installers to program commonly used features quickly and easily.

If complex coding is required, the system also allows programmers to write, save and execute their own codes making it a truly flexible control system for any application.

Ideal for home automation, corporate office controls and large rooms.

Features

- 8 x RS232/485 control ports
 - Port 1 - 4: Bi-directional RS-232/485
 - Port 5-8 : Bi-directional RS-232
- 4 x IR outputs
- 4 x Digital I/O
- 4 x Relay
- Support iOS control app
- Support Ethernet and RS-232 controls

Technical specification

Control Ports:	8 x RS232/485 control ports Port 1 - 4: Bi-directional RS-232/485 Port 5-8 : Bi-directional RS-232 4 x IR outputs 4 x Digital I/O 4 x Relay 1 x Ethernet port
Processing speed:	up to 400MHz
Input voltage:	24V DC 1A
Rack Mountable:	Standard 1U 19 inch chassis