

## ZW-14AWG SPK CB (150M) Speaker Cable



150M

### Features

- Cable Type: 14AWG\*2C Speaker Cable
- Packaging: 150m wooden roll
- Operating Temperature: -20°C THRU 75°C

### Technical specification

#### Materials

Nom. Conductor O.D.:	42*0.256±0.01mm
Conductor Material:	Tinned Copper
Nom. Insulation O.D.:	3.55±0.1mm
Insulation Material:	PVC, Color in Black and White
Nom. Cabling Lay length:	71±10mm
Nom. Jacket O.D.:	9.14±0.3mm
Min Jacket Thickness:	0.85mm
Jacket Material:	Grey PVC, CM
Rip Cord:	3*500D

#### Electrical Characteristics

Nom. Conductor Resistance(@20°C):	≤9.38Ω/km(2.86 Ohm/kft)
Nom. Capacitance Cond-to-Cond	22pF/ft
Max. Current	9.6 Amps Per Cond at 25°C
Voltage Rating	300V
Insulation Resistance(@20°C in Air):	≥200MΩ·km
Insulation Withstanding Spark Voltage:	AC 3000V
Jacket Withstanding Spark Voltage:	AC 3000V

#### Packaging

150m	Roll Size: 370mm(L)*100mm(W)*200mm(H) Pallet: 1110*1110*130mm; 3(L)*3(w)*5(H)=45 rolls/pallet,H=1.13M
------	----------------------------------------------------------------------------------------------------------